

Scanners with native Optix® Drivers

Scanner Model	Platform (Optix Workstation + Driver)	Interface (SCSI / USB)	Scan Style (B&W, Grayscale, Col., Simpl. / Dupl.)	Resolution (dpi)	Min/Max Paper Size (inches)	Max. Transport Speed (ppm)
Canon 3020	Windows	SCSI	B&WS/D	300	2.2 x 2.8 – 10.1 x 14.3	40
Canon DR-3080C	Windows	SCSI	B&W, G, C, S/D	400	2.2 x 2.8 – 10.1 x 14.3	80
Canon 5020	Windows	SCSI	B&W, S/D	400	2.23 x 2.75 – 11.85 x 17	90
Canon 5080C	Windows	SCSI	B&W, G, C, S/D	400	2.25 x 2.75 – 11.85 x 17	90
Fujitsu 620C	Windows, Mac OS X	SCSI	B&W, G, C, S	75-600	3.7 x 5.5 – 8.5 x 14	20
Fujitsu M4097D	Windows, Mac OS X	SCSI	B&W, G, S/D	100-800 (400 optical)	2.1 x 2.9 – 11.7 x 17	50/90
Fujitsu M4099D	Windows, Mac OS X	SCSI	B&W, G, S/D	200-400	2.9 x 4.1 – 11 x 17	90/180
Fujitsu fi-4010CU	Mac OS X	USB2.0	B&W, G, C, S	75-600	4.5 x 5.5 – 8.5 x 14	12
Fujitsu fi-4120C/C2	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.0x2.9-8.5x14	25/25
Fujitsu fi-4220C/C2	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.0x2.9-8.5x14	25/25
Fujitsu fi-4340C	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-800 (600 optical)	2.9 x 4.1 – 8.5 x 14	40/80
Fujitsu fi-4530C	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600 (600 optical)	2.9 x 2.9 – 11.0 x 17	35/35
Fujitsu fi-4750C	Windows, Mac OS X	SCSI	B&W, G, C, S/D	75-600	2.1 x 2.9 – 11.0 x 17.0	50/90
Fujitsu fi-4860C	Windows, Mac OS X	SCSI	B&W, G, C, S/D	75-400	2.9 x 4.1 – 11 x 17	63/125 (P) 73/146 (L)
Fujitsu fi-5110C/EOX/2 ScanSnap	Windows, Mac OS X	USB2.0	B&W, G, C, S/D	75-600	2.9 x 4.1 – 8.5 x 14	15/30
Fujitsu fi-5120C (replaced 4120C)	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.0x2.9-8.5x14	25/25
Fujitsu fi-5220C (replaced 4220C)	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.0x2.9-8.5x14	25/25
Fujitsu fi-6130 (replaced 5120C)	Windows, Mac OS X	USB2.0	B&W, G, C, S/D	75-600	2.0x2.9-8.5x14	40/80
Fujitsu fi-6230 (replaced 5220C)	Windows, Mac OS X	USB2.0	B&W, G, C, S/D	75-600	2.0x2.9-8.5x14	40/80
Fujitsu fi-6140	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.0x2.9-8.5x14	60/120
Fujitsu fi-6240	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.0x2.9-8.5x14	60/120
Fujitsu fi-6670 (replaced 5650C)	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.0 x 3.0 – 11 x 17	70/140 (P) 90/180 (L)
Fujitsu fi-6770 (replaced 5750C)	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.0 x 3.0 – 11 x 17	70/140 (P) 90/180 (L)
Fujitsu fi-5530C	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.1 x 2.9 – 11 x 17	35/70

Fujitsu fi-5650C	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.9 x 4.1 – 11 x 17	57/114 (P) 72/142 (L)
Fujitsu fi-5750C	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.9 x 4.1 – 11 x 17	57/114 (P) 72/142 (L)
Fujitsu fi-5900C	Windows, Mac OS X	SCSI/USB2.0	B&W, G, C, S/D	75-600	2.1 x 2.9 – 12 x 17	100/200 (P) 120/240 (L)
Kodak 2500	Windows	SCSI	B&W, S/D	100-600 (400 optical)	4.7 x 5.3 – 12.2 x 17.0	60
Kodak 3500	Windows	SCSI	B&W, S/D	600	2.5 x 2.511.7W x 16L	75
Kodak 3590C	Windows	SCSI	B&W, C, S/D	600	2.5 x 2.5 – 12W x 26L	85
Kodak 5500	Windows	SCSI	B&W, S/D	100 – 300	2.5 x 2.5 – 12 x 20	80
Contex FSS3000	Windows	SCSI	Large format scanner	400-1800	J-size (36" throat)	1.5-4"/sec.

This document is provided for informational purposes only. Support is also available on Windows 2000/XP for any scanner with an available ISIS driver. Contact Thom Vagt (tv@mindwrap.com) at (703) 242-0360 for details and pricing. We can integrate virtually any scanner with Optix.